

Promat

Promat Australia Pty. Ltd.

SYSTEM CERTIFICATE*

This is to certify that

PROMASEAL® Green Cast In Collars

on pipe penetrations through concrete slabs
have been tested/approved in accordance with

“Australian Standard 1530: Part 4

Methods for fire tests on building materials, components and structures”



Penetration	Element	FRL	Report	Notes
40-100mm uPVC	120mm Concrete	-/180/120	RIR45780.3	With Fitting
40-100mm uPVC	150mm Concrete	-/180/180	RIR45780.3	With Fitting
40mm & 100mm uPVC	80mm concrete	-/90/60	A-14-882	
40mm uPVC	95mm CF210	-/120/90	A-17-075A	With Fitting
100mm uPVC	95mm CF210	-/120/120	A-17-075A	With Fitting
40mm uPVC	120mm Kingfloor	-/240/240	A-07-516	
100mm uPVC	120mm Kingfloor	-/240/120	A-07-516	
40-100mm uPVC	Side of concrete beam	-/180/180	FAR4458	
40-100mm uPVC	Ultrafloor 130R, 150R, 150C	-/180/120	RIR45780.3	
40-100mm uPVC	90mm concrete	-/90/60	FAR4652	

*This is NOT a test certificate. For installation instructions or further information please contact Promat Australia Pty. Ltd.

Dial: 1800 PROMAT (776 628)

Email: mail@promat.com.au

Visit: www.promat.com.au

PROMAT Australia Pty Ltd
1 Scotland Rd Mile End SA 5031
T 1800 PROMAT (776 628)
www.promat.com.au

etex building
performance

Promat

Promat Australia Pty. Ltd.

SYSTEM CERTIFICATE*

Penetration	Element	FRL	Report	Notes
40mm HDPE	120mm Concrete	-/240/120	RIR45780.3	
50mm HDPE	120mm Concrete	-/180/120	RIR45780.3	
65mm HDPE	120mm Concrete	-/240/120	RIR45780.3	
80mm HDPE	120mm Concrete	-/120/120	RIR45780.3	
100mm HDPE	120mm Concrete	-/120/120	RIR45780.3	
40mm HDPE	170mm Concrete	-/240/240	RIR45780.3	
50mm HDPE	170mm Concrete	-/180/180	RIR45780.3	
65mm HDPE	170mm Concrete	-/240/180	RIR45780.3	
80mm HDPE	170mm Concrete	-/120/120	RIR45780.3	
100mm HDPE	170mm Concrete	-/120/120	RIR45780.3	
40mm HDPE	120mm Kingfloor	-/240/120	A-08-525	
100mm HDPE	150m Kingfloor	-/240/180	A-08-555	
100mm HDPE	200mm concrete	-/180/180	A-17-003A	Oversize hole
40-100mm HDPE	Side of concrete beam	-/180/180	FAR4458	
40-100mm HDPE	Ultrafloor 130R, 150R, 150C	-/120/120	RIR45780.3	
40mm Raupiano Plus	120mm Concrete	-/240/180	WFRA 26149-05	
50mm Raupiano Plus	120mm Concrete	-/240/180	WFRA 26149-05	
75mm Raupiano Plus	150mm Concrete	-/240/240	A-16-066	Backfilled with Graf4T
90mm Raupiano Plus	120mm Concrete	-/180/180	WFRA 26149-05	
100mm Raupiano Plus	120mm Concrete	-/180/180	WFRA 26149-05	
16mm PEX	120mm Concrete	-/240/120	A-11-737	Green 40 used
20mm PEX	120mm Concrete	-/240/120	A-11-737	Green 40 used
25mm PEX	120mm Concrete	-/240/120	A-11-737	Green 40 used
32mm PEX	120mm Concrete	-/240/120	A-11-737	Green 40 used
40mm PPR	120mm Kingfloor	-/240/120	A-08-525	
50mm PPR	120mm Concrete	-/240/180	WFRA2159700	
100mm PPR	120mm Concrete	-/240/120	WFRA2159700	
56mm Wavin Astolan	120mm Concrete	-/120/120	WFRA27884300.1	Green 65 used
100mm Wavin Astolan	120mm Concrete	-/120/120	WFRA27884300.1	

*This is NOT a test certificate. For installation instructions or further information please contact Promat Australia Pty. Ltd.

Dial: 1800 PROMAT (776 628)

Email: mail@promat.com.au

Visit: www.promat.com.au

PROMAT Australia Pty Ltd
 1 Scotland Rd Mile End SA 5031
 T 1800 PROMAT (776 628)
www.promat.com.au

etex building
 performance